

SOLAR PEDESTRIAN FLASHER SYSTEM

Commercial-Grade Solar-Powered Warning Beacon & Flasher System

TECHNICAL SPECIFICATIONS

Solar Charging Panel	20W, 18V Monocrystalline Silicon Panel
Battery System	High-Capacity Lithium Battery (12V / 8800 mAh)
Flash Pattern	WWS (Wig-Wag Steady) Pattern
Working Mode	Push Button Activation
Activation Window	Flashing lights automatically stop 60 seconds after button is pushed
Operating Autonomy	Up to 12 hours of continuous operation when fully charged
Battery Design Life	3 to 5 Years
Standard Hardware	Fits 3" to 4" diameter posts (round/square)*
Shipping Weight	11.5 kg (approx. 25.3 lbs)

COMPONENT DIMENSIONS

PUSH BUTTON UNIT 4.5" W x 8.5" H x 2.25" L	SOLAR PANEL 9.75" W x 14" H x 0.75" L	RFB MODULE 17.5" W x 2.5" H x 2.75" L
---	--	--

HARDWARE COMPATIBILITY

Standard Pole Mount

Fits securely on any 3" to 4" diameter mounting post.

WARRANTY COVERAGE

2-Year Full Warranty

Full manufacturer warranty covering components and performance.

* Standard mounting hardware is included for immediate installation on standard 3"-4" posts. Performance may vary based on geographic location and seasonal sunlight exposure.